

INVERTER

AUX
AIR CONDITIONER

MA-SERIES^{NEW}

ประหยัด ทนทาน เย็นเร็วไม่ต้องรอ



GENTLE WIND

สัมผัสสายลมเย็น นุ่มนวล ในโหมด Gentle Wind
ผ่อนคลาย เหมือนอยู่ท่ามกลางธรรมชาติ



Easy Installation



4D Airflow



iClean



iFeel



Anti-Corrosion



รับประกันตัวเครื่อง 5 ปี
รับประกันคอมเพรสเซอร์ 10 ปี
ฟรี! ค่าบริการ ค่าแรง ค่าอะไหล่

หมายเหตุ : ไม่รวมภาษีมูลค่าเพิ่ม



MA-SERIES

MA Series Specification

Series				DC Inverter R32				
Model Indoor Model outdoor				ASW-09/DIMA W-09/DIMA	ASW-13/DIMA W-13/DIMA	ASW-18/DIMA W-18/DIMA	ASW-24/DIMA W-24/DIMA	
Rated Capacity		Cooling	W BTU/hr	2700(600-3200) 9000	3550(800-4100) 12000	5300(1300-5600) 18000	7000(1800-7600) 24000	
Rated Power Consumption			W	820(400-1600)	1180(400-1600)	1730(290-2100)	2200(230-2500)	
Rated Running Current			A	3.9(1.7-7.2)	5.6(1.7-7.2)	7.9(2.2-9.6)	10.3(1.0-11.5)	
SEER			BTU/W.h	17.06	17.06	17.30	17.91	
Standard EGAT No.5 Label Ranking								
INDOOR UNIT	Power Supply		Ph/ V /Hz	1/220/50	1/220/50	1/220/50	1/220/50	
	Air Direction			Up-Down-Left-Right Auto Swing				
	Indoor Unit Weight (Net)		Kg	8	8	11	12.5	
	Evaporator	Tube	Material	/	Copper	Copper	Copper	Copper
		Fin	Material	/	Hydrophilic foil	Hydrophilic foil	Hydrophilic foil	Hydrophilic foil
	Fan system		Fan	Motor Fancoil	DC MOTOR	DC MOTOR	DC MOTOR	DC MOTOR
	Dimension	Net Dimension (WxDxH)		mm	768×299×200	768×299×200	997×321×222	1140×334×229
		Packing Dimension (WxDxH)		mm	831×371×282	831×371×282	1070×385×312	1210×400×327
Connection		Liquid Pipe		mm	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")
		Gas Pipe		mm	9.52(3/8")	9.52(3/8")	12.7 (1/2")	15.88 (5/8")
OUTDOOR UNIT	Compressor Type		/	Rotary	Rotary	Rotary	Rotary	
	Refrigerant		/	R32	R32	R32	R32	
	Refrigerant Charged		g	370	450	750	1120	
	Outdoor Unit Weight (Net)		Kg	17	21	26	40	
	Condenser	Tube	Material	/	Copper	Copper	Copper	Copper
		Fin	Material	/	Hydrophilic foil	Hydrophilic foil	Hydrophilic foil	Hydrophilic foil
	Dimension	Net Dimension (WxDxH)		mm	650×455×233	709×536×280	785×555×300	900×700×350
		Packing Dimension (WxDxH)		mm	760×510×315	825×595×345	903×615×382	1015×762×425